

Radian's NEW Professional Installation Series

With the growing demand for surface mounted speaker that are both high quality and cost effective. Radian Audio Engineering is thrilled to bring you the RC-500. This Professional Installation Series has been the focus of our Engineering department. Radian Audio Engineering has always strived to go beyond the industry standard of quality and price. With the RC-500, Radian Audio has bridged such a gap. The RC-500 is the obvious choice for today's demanding church, theatre, restaurants, and home theatre.

Frequency Range: 80Hz - 19kHz
Power Handling: 10-80W
Nominal Sensitivity: 90dB SPL, 1W @ 1m (3.3ft)
Rated Maximum SPL: 107 dB, 1W @ 1m (3.3ft)
Nominal Impedance: 8 Ohms
Transformer Taps: 70V: 15W, 7.5W, 5W, 2.5W, 1.25W
100V: 15W, 7.5W, 5W, 2.5W
8 Ohm Thru
Low-Frequency: 135mm(5 1/4in) glue paper cone
1" coil on aluminum former
High-Frequency: 13.25mm(1/2in) polyester
Enclosure: Box: High impact polystyrene
Measurement(WxDxH): 210mm x 190mm x 286mm (8.26in x 7.48in x 11.2in)
Net weight(each): 2.73kg (6.01 lb)
Included Accessories: U-bracket



- Weather resistant for both indoor and outdoor use.
- Two way speaker system for extended frequency response (5 1/4" woofer and 1/2" tweeter).
- Adjustable 70/100 volt variable wattage taps for installation in both commercial and residential applications. Also, with an option for 8 ohm thru.
- Steel swivel U-bracket for easy vertical and horizontal mounting on walls, corners, ceilings, and more.
- Small enclosures that save space but are still big on sound.