



## RPS-115 & RPS-215

### PROFESSIONAL SERIES: 15" SUBWOOFER SYSTEMS


Radian's RP Series subwoofer systems are designed specifically for touring/live sound system applications. The RPS-115, single 15", and RPS-215, a dual 15", are designed to provide extended low-frequency response for high SPL live and playback applications.

Both the RPS-115 and RPS-215 feature a composite ribbed cone reinforced with Kevlar®. The 4" voice coil is edgewound aluminum for better transient response, but advanced adhesives give it the power handling capacity of more conventional copper voice coils. The RPS-115 and RPS-215 are capable of genuine 124-127 dB SPL, from 40 Hz to 500 Hz or 35 Hz to 500 Hz with 6 dB to spare for peak output.

Add this to a high-energy magnetic structure with a venturi cross section to increase efficient ventilation, and the result is a highly responsive subwoofer system that delivers robust bass at high SPLs.



- ✓ **VENTED DESIGN**
- ✓ **KEVLAR® IMPREGNATED CONE**
- ✓ **4" VOICE COIL**
- ✓ **LOW DISTORTION**
- ✓ **HIGH SENSITIVITY**
- ✓ **DURADIAN™ FINISH**



# RPS-115 & RPS-215



## PROFESSIONAL SERIES: 15" SUBWOOFER SYSTEMS


### SPECIFICATIONS

#### RPS-115

#### RPS-215


FREQUENCY RESPONSE . . . . .	40 Hz – 500 Hz . . . . .	35 Hz – 500 Hz
POWER HANDLING . . . . .	600 watts RMS. . . . .	1200 watts RMS
SENSITIVITY* . . . . .	96 dB . . . . .	99 dB
IMPEDANCE . . . . .	8 ohms . . . . .	4 ohms
MAX SPL. . . . .	124 dB continuous, . . . . . 130 dB peak	127 dB continuous, 133 dB peak
DIMENSIONS (HWD). . . . .	27-1/2" x 20-1/8" x 20", . . . . . 680 x 511 x 580 mm	21-1/8" x 44" x 20-1/4", 536 x 1117 x 514 mm
ENCLOSURE CONSTRUCTION. .	13-ply Baltic birch, handle, . . . front-to-rear bracing to reduce cabinet resonance	13-ply Baltic birch, handle, front-to-rear bracing to reduce cabinet resonance
INPUT CONNECTORS. . . . .	Dual NL4 Neutrik Speakon . . .	Dual NL4 Neutrik Speakon
STANDARD FINISH . . . . .	Scratch-resistant, waterproof . . black Duradian™ finish	Scratch-resistant, waterproof black Duradian™ finish
NET WEIGHT. . . . .	84 lbs., 38 kg . . . . .	134 lbs., 61 kg
SHIPPING WEIGHT . . . . .	92 lbs., 41.8 kg . . . . .	142 lbs., 65 kg

\*One Watt, One Meter



RPS-215 →

← RPS-115



Specifications subject to change without notice.

#### LIMITED WARRANTY

Radian Audio Engineering, Inc. products, when sold domestically, are guaranteed for a period of five (5) years from the date of original purchase against malfunctions due to defects in workmanship. If such a malfunction occurs, the product will be repaired or replaced at our option, without charge, if delivered prepaid to the factory. Product will be returned prepaid via ground transport. This warranty does not extend to damage resulting from improper installation, misuse, neglect or abuse. The warranty does not apply to external finish or appearance. The warranty does not apply to burnt voice coils. In no event shall Radian Audio Engineering, Inc. be liable for incidental or consequential damages including, without limitation, injury to persons or property or loss of use.

600 N. Batavia Street

Orange, CA 92868

Phone: (714) 288-8900

Fax: (714) 288-1133

E-mail: [radian@radianaudio.com](mailto:radian@radianaudio.com)

Web: [www.radianaudio.com](http://www.radianaudio.com)