


Radian's RP Series two-way, full-range coaxial loudspeaker systems are designed specifically for touring/portable sound systems. The RPX-112P-V, a passive coaxial loudspeaker system, and the RPX-112B-V bi-amp model are loaded with an 12" low-frequency woofer and 2" exit compression driver for main system or playback usage in live sound applications.

Unlike traditional multi-way loudspeaker systems that employ separate low frequency speakers with compression driver/horn combinations, Radian coaxial loudspeaker systems present all frequencies to the audience from one coherent source. This single-point source system eliminates the problem often associated with "time smear" in which the sound coming from the low-frequency component arrives at the listener's ear earlier or later than the sound emanating from the horn/driver combination.

Radian loudspeaker systems' conical dispersion patterns utilize the low-frequency cone as an extension of the high-frequency compression driver to provide clean, transparent reproduction of both music and speech with lower distortion than most asymmetrical high-frequency horns.

Radian RP Series full-range loudspeaker system enclosures have 20 degree sides and are trapezoidal in shape. Construction is of 3/4" 13-ply Baltic birch protected with Radian's exclusive scratch-resistant Duradian™ finish. All systems have dual/parallel Neutrik NL4 Speakon input connectors.



- ✓ **PASSIVE OR BI-AMP OPERATION**
- ✓ **COMPACT, PORTABLE**
- ✓ **TRUE POINT SOURCE**
- ✓ **500 WATTS RMS**
- ✓ **90° CONICAL DISPERSION**
- ✓ **DURADIAN FINISH™**

RPX-112P-V/B-V



PROFESSIONAL SERIES: 12Ó TWO-WAY ARRAYABLE LOUDSPEAKER SYSTEM

SPECIFICATIONS

FREQUENCY RESPONSE 55 Hz ÷ 20 kHz
POWER HANDLING 500 watts RMS
SENSITIVITY 96 dB
IMPEDANCE** P = 8 ohms, B = 8 ohms LF, 8 ohms HF
MAX SPL 123 dB continuous, 129 dB peak
NOMINAL DISPERSION 90¼ Conical
DIMENSIONS(HWD) 24-1/2Ó x 17-3/4Ó x 17-1/2Ó,
622 x 451 x 445 mm
ENCLOSURE CONSTRUCTION 3/4Ó 13-ply Baltic birch with
perforated steel grills, handle, and
bottom pole cup for stand mounting
INPUT CONNECTORS Dual/parallel Neutrik NL4 Speakon
FLY POINTS Sixteen 3/8Ó-16


STANDARD FINISH Scratch-resistant, waterproof black
Durathane™ finish

NET WEIGHT

SHIPPING WEIGHT

*One Watt, One Meter

** P = Passive only B = Bi-amp only



Specifications subject to change without notice.

LIMITED WARRANTY

Radian Audio Engineering, Inc. products, when sold domestically, are guaranteed for a period of five (5) years from the date of original purchase against malfunctions due to defects in workmanship. If such a malfunction occurs, the product will be repaired or replaced at our option, without charge, if delivered prepaid to the factory. Product will be returned prepaid via ground transport. This warranty does not extend to damage resulting from improper installation, misuse, neglect or abuse. The warranty does not apply to external finish or appearance. The warranty does not apply to burnt voice coils. In no event shall Radian Audio Engineering, Inc. be liable for incidental or consequential damages including, without limitation, injury to persons or property or loss of use.

600 N. Batavia Street
Orange, CA 92868
Phone: (714) 288-8900
Fax: (714) 288-1133
E-mail: radian@radiaudio.com
Web: www.radiaudio.com